

Serre-fil à sertir de réduction (DIN 46267) type PVD-R, étanche

pour câbles avec conducteurs en cuivre de sections différentes

Sur demande, serre-fil pour d'autres coupes transversales

Exécution

cuivre étamé



Article n°	Type	Section mm ²	a mm	d1 mm	d2 mm	Code de presse
64471	PVD-R 16/6	16/6	55	5.5	3.8	8
64365	PVD-R 16/10	16/10	55	5.5	4.5	8
64366	PVD-R 25/10	25/10	55	7.0	4.5	10
64367	PVD-R 25/16	25/16	55	7.0	5.5	10
64368	PVD-R 35/16	35/16	55	8.2	5.5	12
64369	PVD-R 35/25	35/25	55	8.2	7.0	12
64922	PVD-R 50/16	50/16	60	10.0	5.5	14
64370	PVD-R 50/25	50/25	60	10.0	7.0	14
64371	PVD-R 50/35	50/35	60	10.0	8.2	14
64373	PVD-R 70/50	70/50	60	11.5	10.0	16
58850	PVD-R 95/25	95/25	75	13.5	7.0	18
64374	PVD-R 95/50	95/50	75	13.5	10.0	18
64375	PVD-R 95/70	95/70	75	13.5	11.5	18
64376	PVD-R 120/50	120/50	75	15.5	10.0	20
64378	PVD-R 120/95	120/95	75	15.5	13.5	20
58852	PVD-R 150/50	150/50	85	17.0	8.2	22
64379	PVD-R 150/70	150/70	85	17.0	11.5	22
64380	PVD-R 150/95	150/95	85	17.0	13.5	22
64381	PVD-R 150/120	150/120	85	17.0	15.5	22
64384	PVD-R 185/150	185/150	90	19.0	17.0	25
64385	PVD-R 240/120	240/120	95	21.5	15.5	28
64386	PVD-R 240/150	240/150	95	21.5	17.0	28
64387	PVD-R 240/185	240/185	95	21.5	19.0	28
64388	PVD-R 300/150	300/150	105	24.5	17.0	32
64389	PVD-R 300/185	300/185	105	24.5	19.0	32
64390	PVD-R 300/240	300/240	105	24.5	21.5	32