

## Fixing Clamps

# Clamp type BFBT 1

### Composed of


Body made of cast aluminium with stainless steel A2 bolts and rubber insert, including fastening bolts

### To provide with PO's

Type of fixing  
Cable diameter  
Cable type

### To order separately:

Supporting cross type STKR  
Profile rail type PS  
Slot nut type PSVN



Dimension	a mm	b mm	e mm	h mm	Screws mm	Drawing
1040 - 1073	60	160	130	60	M 12 x 160	S1467-4
2068 - 2088	65	175	145	60	M 12 x 170	S1468-4
3083 - 3108	75	200	170	60	M 12 x 190	S1469-4
4103 - 4133	90	245	210	80	M 16 x 220	S1470-4
5128 - 5148	100	255	220	100	M 16 x 240	S1471-4

Part no	Type	Cable Ø mm	Part no	Type	Cable Ø mm
88850	BFBT1-1040	37.6 - 40.0	88723	BFBT1-3095	92.6 - 95.0
88851	BFBT1-1043	40.1 - 42.5	88724	BFBT1-3098	95.1 - 97.5
88852	BFBT1-1045	42.6 - 45.0	88725	BFBT1-3100	97.6 - 100.0
88853	BFBT1-1048	45.1 - 47.5	88726	BFBT1-3103	100.1 - 102.5
88854	BFBT1-1050	47.6 - 50.0	88727	BFBT1-3105	102.6 - 105.0
88700	BFBT1-1053	50.0 - 52.5	88728	BFBT1-3108	105.1 - 107.5
88701	BFBT1-1055	52.6 - 55.0	88729	BFBT1-4103	100.1 - 102.5
88702	BFBT1-1058	55.1 - 57.5	88730	BFBT1-4105	102.6 - 105.0
88703	BFBT1-1060	57.6 - 60.0	88731	BFBT1-4108	105.1 - 107.5
88704	BFBT1-1063	60.1 - 62.5	88732	BFBT1-4110	107.6 - 110.0
88705	BFBT1-1065	62.6 - 65.0	88733	BFBT1-4113	110.1 - 112.5
88706	BFBT1-1068	65.1 - 67.5	88734	BFBT1-4115	112.6 - 115.0
88707	BFBT1-1070	67.6 - 70.0	88735	BFBT1-4118	115.1 - 117.5
88708	BFBT1-1073	70.1 - 72.5	88736	BFBT1-4120	117.6 - 120.0
88709	BFBT1-2068	65.1 - 67.5	88737	BFBT1-4123	120.1 - 122.5
88710	BFBT1-2070	67.6 - 70.0	88738	BFBT1-4125	122.6 - 125.0
88711	BFBT1-2073	70.1 - 72.5	88739	BFBT1-4128	125.1 - 127.5
88712	BFBT1-2075	72.6 - 75.0	88740	BFBT1-4130	127.6 - 130.0
88713	BFBT1-2078	75.1 - 77.5	88741	BFBT1-4133	130.1 - 132.5
88714	BFBT1-2080	77.6 - 80.0	88742	BFBT1-5128	125.1 - 127.5
88715	BFBT1-2083	80.1 - 82.5	88743	BFBT1-5130	127.6 - 130.0
88716	BFBT1-2085	82.6 - 85.0	88744	BFBT1-5133	130.1 - 132.5
88717	BFBT1-2088	85.1 - 87.5	88745	BFBT1-5135	132.6 - 135.0
88718	BFBT1-3083	80.1 - 82.5	88746	BFBT1-5138	135.1 - 137.5
88719	BFBT1-3085	82.6 - 85.0	88747	BFBT1-5140	137.6 - 140.0
88720	BFBT1-3088	85.1 - 87.5	88748	BFBT1-5143	140.1 - 142.5
88721	BFBT1-3090	87.6 - 90.0	88749	BFBT1-5145	142.6 - 145.0
88722	BFBT1-3093	90.1 - 92.5	88750	BFBT1-5148	145.1 - 147.5