

Conductor and insulation preparation

Insulation pushing device set up to 800 mm²

Application

The insulation pushing device set is applied to push back the insulation of polymeric cables with cross sections up to 800 mm².

Technical Data

- Conductor cross-section: 240 - 800 mm²
- Material: Stainless steel

Scope of delivery

- 2 Insulation pushing devices
- 6 Pair of pressure discs
- 5 Pair of adapter sleeves
- Lubricant type Metaflux
- Packaging, Wooden box (38 x 27 x 15 cm)



Ordering information

| Part no | Type | Description | Weight kg |
|---------|---------------------------|-------------------------------|-----------|
| 88957 | 240 - 800 mm ² | Insulation pushing device set | 16.0 |

Spare parts

| Part no | Type | Description | Weight kg |
|---------|---------------------------|--------------------------------------|-----------|
| 78168 | 240 mm ² | Pressure disc with inner Ø 19.8 mm | 0.24 |
| 78169 | 300 mm ² | Pressure disc with inner Ø 22.5 mm | 0.23 |
| 78170 | 400 mm ² | Pressure disc with inner Ø 25.5 mm | 0.26 |
| 78171 | 500 mm ² | Pressure disc with inner Ø 28.5 mm | 0.28 |
| 78172 | 630 mm ² | Pressure disc with inner Ø 32.5 mm | 0.31 |
| 78173 | 800 mm ² | Pressure disc with inner Ø 38 mm | 0.32 |
| 78159 | 240 mm ² | Adapter sleeves with inner Ø 19.8 mm | 0.43 |
| 78160 | 300 mm ² | Adapter sleeves with inner Ø 22.5 mm | 0.40 |
| 78161 | 400 mm ² | Adapter sleeves with inner Ø 25.5 mm | 0.33 |
| 78162 | 500 mm ² | Adapter sleeves with inner Ø 28.5 mm | 0.26 |
| 78163 | 630 mm ² | Adapter sleeves with inner Ø 32.5 mm | 0.16 |
| 78179 | 240 - 800 mm ² | Sliding disc | 0.01 |
| 78157 | 240 - 800 mm ² | Fixing part | 0.66 |
| 78158 | 240 - 800 mm ² | Press part | 0.60 |
| 78183 | 209 | Handle bar complete | 0.08 |
| 79249 | Metaflux | Lubricant | 0.01 |