

Conductor and insulation preparation

Insulation pushing device set up to 800 mm²

Application

The insulation pushing device set is applied to push back the insulation of polymeric cables with cross sections up to 800 mm².

Technical Data

- Conductor cross-section: 240 - 800 mm²
- Material: Stainless steel

Scope of delivery

- 2 Insulation pushing devices
- 6 Pair of pressure discs
- 5 Pair of adapter sleeves
- Lubricant type Metaflux
- Packaging, Wooden box (38 x 27 x 15 cm)



Ordering information

Part no	Type	Description	Weight kg
88957	240 - 800 mm ²	Insulation pushing device set	16.0

Spare parts

Part no	Type	Description	Weight kg
78168	240 mm ²	Pressure disc with inner Ø 19.8 mm	0.24
78169	300 mm ²	Pressure disc with inner Ø 22.5 mm	0.23
78170	400 mm ²	Pressure disc with inner Ø 25.5 mm	0.26
78171	500 mm ²	Pressure disc with inner Ø 28.5 mm	0.28
78172	630 mm ²	Pressure disc with inner Ø 32.5 mm	0.31
78173	800 mm ²	Pressure disc with inner Ø 38 mm	0.32
78159	240 mm ²	Adapter sleeves with inner Ø 19.8 mm	0.43
78160	300 mm ²	Adapter sleeves with inner Ø 22.5 mm	0.40
78161	400 mm ²	Adapter sleeves with inner Ø 25.5 mm	0.33
78162	500 mm ²	Adapter sleeves with inner Ø 28.5 mm	0.26
78163	630 mm ²	Adapter sleeves with inner Ø 32.5 mm	0.16
78179	240 - 800 mm ²	Sliding disc	0.01
78157	240 - 800 mm ²	Fixing part	0.66
78158	240 - 800 mm ²	Press part	0.60
78183	209	Handle bar complete	0.08
79249	Metaflux	Lubricant	0.01