

## Conductor and insulation preparation

# Insulation pushing device set 1000–2500 mm<sup>2</sup>

### Application

The insulation pushing device set is applied to push back the insulation of polymeric cables with cross sections from 1000 mm<sup>2</sup> up to 2500 mm<sup>2</sup>.

### Technical Data

- Conductor cross-section: 1000 - 2500 mm<sup>2</sup>
- Material: Stainless steel

### Scope of delivery

- Insulation pushing device
- 5 Pair of pressure discs
- 4 Pair of adapter sleeves
- Lubricant type Metaflux
- Packaging, Wooden box (47 x 30 x 15 cm)



### Ordering information

Part no	Type	Description	Weight kg
88958	1000 - 2500 mm <sup>2</sup>	Insulation pushing device set	23.5

### Spare parts

Part no	Type	Description	Weight kg
78174	1000 mm <sup>2</sup>	Pressure disc with inner Ø 42 mm	0.36
78175	1200 mm <sup>2</sup>	Pressure disc with inner Ø 45.5 mm	0.38
78176	1600 mm <sup>2</sup>	Pressure disc with inner Ø 51 mm	0.40
78177	2000 mm <sup>2</sup>	Pressure disc with inner Ø 58 mm	0.46
78178	2500 mm <sup>2</sup>	Pressure disc with inner Ø 65 mm	0.48
78164	1000 mm <sup>2</sup>	Adapter sleeves with inner Ø 42 mm	1.12
78165	1200 mm <sup>2</sup>	Adapter sleeves with inner Ø 45.5 mm	0.96
78166	1600 mm <sup>2</sup>	Adapter sleeves with inner Ø 51 mm	0.70
78167	2000 mm <sup>2</sup>	Adapter sleeves with inner Ø 58 mm	0.30
78180	1000 - 2500 mm <sup>2</sup>	Sliding disc	0.02
78181	1000 - 2500 mm <sup>2</sup>	Fixing part	1.20
78182	1000 - 2500 mm <sup>2</sup>	Press part	0.90
78183	209	Handle bar complete	0.08
79249	Metaflux	Lubricant	0.01