

Assembly of silicone parts

Pulling device set for Terminations

Application

The pulling device set is used to pull-on silicone stress cones type STRC on polymer cables during the assembly of HV cable terminations.

Technical Data

Manual hoist:

- Rated force: 600 kg
- Overload protection: 900 kg
- Wire feed per double stroke: 30 mm
- Load on lever at rated load: 25 kg
- Wire diameter: 6.4 mm
- Wire length: 10 m
- Length of wire rope strap: 1 m

Scope of delivery

- 2 pieces of manual hoists of type "Habegger Hit-6"
- Box with adapter rings to pull-on the stress cones of type STRC
- Packaging, Wooden box (50 x 45 x 37 cm)



Ordering information

Part no	Type	Description	Weight kg
88299	50 - 126 mm	Pulling Device Set	40.0

Spare parts

Part no	Type	Description	Weight kg
76283	58 mm	Adapter ring	0.10
76289	62 mm	Adapter ring	0.11
76284	66 mm	Adapter ring	0.15
76290	70 mm	Adapter ring	0.12
76285	74 mm	Adapter ring	0.13
76291	78 mm	Adapter ring	0.13
76286	82 mm	Adapter ring	0.14
76292	86 mm	Adapter ring	0.14
76287	90 mm	Adapter ring	0.14
76293	94 mm	Adapter ring	0.16
76288	98 mm	Adapter ring	0.20
76294	102 mm	Adapter ring	0.16
62126	110 mm	Adapter ring	0.18
78058	118 mm	Adapter ring	0.20
78059	126 mm	Adapter ring	0.20
76155	Habegger Hit-6	2 pieces of manual hoists	7.40
76282		Retaining ring	1.45