

Slide-on conductor ring

Application

The conductor ring is required to fix the slide-on cone onto the prepared cable end. The proper size of the conductor ring is selected according to the diameter of the cable conductor of the prepared cable end:

$$D_{\text{ring}} > D_{\text{con}} + 2 \text{ mm}$$

Note: Please attend the necessary thread size of the conductor ring according to the selected slide-on cone.



Scope of delivery

- Single conductor ring
- Packaging, cardboard box

Ordering information

Part no	Diameter mm	Cross section mm ²	Thread	Description	Part of Set	Weight kg
76202	19.5	240	M42 x 2	Conductor ring	1	0.28
76203	21.8	300	M42 x 2	Conductor ring	1	0.26
76259	24.9	400	M42 x 2	Conductor ring	1	0.22
76204	24.9	400	M50 x 2	Conductor ring	1	0.40
76205	27.8	500	M50 x 2	Conductor ring	1	0.36
60111	28.5	550	M42 x 2	Conductor ring	-	0.35
76206	32.0	630	M50 x 2	Conductor ring	1	0.30
76207	32.0	630	M65 x 2	Conductor ring	1	0.70
60112	34.5	800	M50 x 2	Conductor ring	-	0.65
76208	36.8	800	M65 x 2	Conductor ring	1	0.62
76209	42.5	1000	M65 x 2	Conductor ring	1	0.52
76210	46.0	1200	M65 x 2	Conductor ring	1	0.44
62155	46.0	1200	M75 x 2	Conductor ring	1	0.76
64249	52.2	1600	M65 x 2	Conductor ring	1	0.30
76211	52.2	1600	M75 x 2	Conductor ring	1 + 2	0.64
76212	62.0	2000	M75 x 2	Conductor ring	1 + 2	0.36
64195	65.0	2500	M75 x 2	Conductor ring	2	0.28
64196	65.0	2500	M80 x 2	Conductor ring	2	0.44