

Slide-on ring with gas valve

Application

The slide-on ring with integrated valve allows the gas injection underneath silicone joint bodies during the slide-on installation process. The proper ring size is selected according to the diameter of the outer semi-conductive layer of the cable where the joint body must be brought into parking position:
 $D_i = D_{sc} + 1 \dots 5 \text{ mm}$



Scope of delivery

- Single slide-on ring
- Packaging, cardboard box

Ordering information

Part no	Diameter mm	Description	Part of Set	Weight kg
76166	60.0	Slide-on ring	1	0.50
76167	65.0	Slide-on ring	1	0.50
76168	70.0	Slide-on ring	1	0.52
76169	75.0	Slide-on ring	1	0.54
76170	80.0	Slide-on ring	1	0.58
76171	85.0	Slide-on ring	1	0.62
76172	90.0	Slide-on ring	1	0.62
76173	95.0	Slide-on ring	1	0.68
76174	100.0	Slide-on ring	1	0.70
76175	105.0	Slide-on ring	1	0.72
76176	110.0	Slide-on ring	1	0.74
64240	115.0	Slide-on ring	2	2.62
64241	120.0	Slide-on ring	2	2.72
64199	125.0	Slide-on ring	2	2.82
64200	130.0	Slide-on ring	2	2.90
77154	132.0	Slide-on ring	2	2.96
77128	135.0	Slide-on ring	2	3.02