

Cable pulling eyes

Pulling set type ZS for corrugated sheath cables

for pulling of single core polymeric cables with corrugated sheath

Technical Data

Max permissible tensile force for Cu conductors = 60 N/mm²
Max permissible tensile force for Al conductors = 30 N/mm²

Composed of

Pulling piece, self-tapping screws, heat shrink tube and sealing tape



Ordering information

Part no	Type	Min. Ø conductor mm	Max. Ø conductor mm	Equivalent conductor cross section mm ²	Press die size
88641	ZS 240	16.0	18.5	240	28
88642	ZS 300	18.5	21.0	300	32
88643	ZS 400	21.0	24.5	400	38
88644	ZS 500	24.5	28.0	500	38
88645	ZS 630	28.0	31.5	630	42
88646	ZS 800	31.5	35.0	800	44
88647	ZS 1000-1	35.0	38.5	1000	52
88648	ZS 1000-2	38.5	42.0	1000	52
88649	ZS 1200	42.0	45.5	1200	60
88650	ZS 1400	45.5	49.0	1400	60
88651	ZS 1600	49.0	52.5	1600	65
88652	ZS 1800	52.5	56.0	1800	70
88654	ZS 2000	56.0	59.5	2000	70
88655	ZS 2500	59.5	64.0	2500	75